Vehicle lighting manufacturer

group of lamps

Universal **LED** rear lamp – low power consumption european E9 homologation ElectroMagnetic Compatibility – **EMC** certificate shock-resistance – **PC** lampshade reverse polarity protection system the depth of the lamp is only 30 mm

LAMP FUNCTIONS:

- rear position light (FT-222 LED)
- number plate light(FT-222 LED)
- STOP light (FT-222 LED)
- indicator (FT-222 LED) reversing light (FT-224 LED)
- fog light (FT-223 LED)
- front position light (FT-225 LED)
- front indicator (FT-225 LED)

TECHNICAL SPECIFICATION:


- supply voltage: 12-15V DC
- operating temperature -40°C to +55°C
- lamp is resistant to any weather conditions
- lamp is fully airtight IP68

POWER CONSUMPTION:

- rear position light + number plate light: 12V = 0,1A
- version without number plate light: 12V = 0,05A
- STOP light: 12V = 0,2A
- indicator: 12V = 0,2A
- reversing light: 12V = 0,2A (FT-224 LED)
- fog light: 12V = 0,2A (FT-223 LED) front position light: 12V = 0,1A (FT-225 LED)

POWER CONSUMPTION (RATED POWER):

- rear position light + number plate light: 12V = 1,2W
- version without number plate lightj: 12V = 0,6W
- STOP light: 12V = 2,4W
- indicator: 12V = 2.4W
- reversing light: 12V = 2,4W (FT-224 LED)
- fog light: 12V = 2,4W (FT-223 LED)
- front position light: 12V = 1,2W (FT-225 LED)





FT-222 LED

3-functional LED rear lamp (STOP/POSITION/INDICATOR)

FT-222 T LED

4-functional LED rear lamp (STOP/POSITION/INDICATOR) with number plate light



FT-223 LED

LED fog lamp



FT-224 LED

LED reversing lamp



FT-225 LED

2-functional LED headlamp with indicator

