

# PRODUCT FAMILY DATASHEET

## DAMP PROOF COMPACT IP66

Damp-proof luminaire, through-wired (L, N, E)



---

### Areas of application

- Industrial and storage facilities
- Car parks and underpasses
- Garages
- Workshops, assembly lines

---

### Product benefits

- Evenly distributed light
- Energy savings of up to 50 % (compared to luminaires that use fluorescent lamps)
- Easy installation as mounting brackets can be positioned freely on the luminaire
- Easy access to electrical terminal thanks end caps with twist and lock mechanism
- Tool-free electrical connection due to push button connector
- 5 years guarantee

---

### Product features

- High luminous efficacy: up to 120 lm/W
- Type of protection: IP66
- Beam angle: 120°
- Through-wiring 3x1.5mm<sup>2</sup> already installed
- Polycarbonate housing



## TECHNICAL DATA

## Electrical data

| Product description                | Nominal wattage | Nominal voltage | Mains frequency | Nominal current | Inrush current |
|------------------------------------|-----------------|-----------------|-----------------|-----------------|----------------|
| DP COMPACT 1200 23W/3000K IP66 GR  | 23.00 W         | 220...240 V     | 50...60 Hz      | 130 mA          | 11 A           |
| DP COMPACT 1200 23 W 4000K IP66 GR | 23.00 W         | 220...240 V     | 50...60 Hz      | 130 mA          | 11 A           |
| DP COMPACT 1500 31W/3000K IP66 GR  | 31.00 W         | 220...240 V     | 50...60 Hz      | 170 mA          | 13 A           |
| DP COMPACT 1500 31 W 4000K IP66 GR | 31.00 W         | 220...240 V     | 50...60 Hz      | 170 mA          | 13 A           |
| DP COMPACT 1200 44W/3000K IP66 GR  | 44.00 W         | 220...240 V     | 50...60 Hz      | 240 mA          | 12 A           |
| DP COMPACT 1200 44 W 4000K IP66 GR | 44.00 W         | 220...240 V     | 50...60 Hz      | 240 mA          | 12 A           |
| DP COMPACT 1200 44 W 6500K IP66 GR | 44.00 W         | 220...240 V     | 50...60 Hz      | 240 mA          | 12 A           |
| DP COMPACT 1500 55W/3000K IP66 GR  | 55.00 W         | 220...240 V     | 50...60 Hz      | 300 mA          | 13 A           |
| DP COMPACT 1500 55 W 4000K IP66 GR | 55.00 W         | 220...240 V     | 50...60 Hz      | 300 mA          | 13 A           |
| DP COMPACT 1500 55 W 6500K IP66 GR | 55.00 W         | 220...240 V     | 50...60 Hz      | 300 mA          | 13 A           |

| Product description                | Inrush current time $T_{h50}$ | Max. no. of lum. on circuit break. B16 A | Max. no. of lum. on circuit break. C10 A | Max. no. of lum. on circuit break. C16 A | Power factor $\lambda$ |
|------------------------------------|-------------------------------|------------------------------------------|------------------------------------------|------------------------------------------|------------------------|
| DP COMPACT 1200 23W/3000K IP66 GR  | 160 $\mu$ s                   | 37                                       | 31                                       | 50                                       | > 0.90                 |
| DP COMPACT 1200 23 W 4000K IP66 GR | 160 $\mu$ s                   | 37                                       | 31                                       | 50                                       | > 0.90                 |
| DP COMPACT 1500 31W/3000K IP66 GR  | 140 $\mu$ s                   | 46                                       | 36                                       | 59                                       | > 0.90                 |
| DP COMPACT 1500 31 W 4000K IP66 GR | 140 $\mu$ s                   | 46                                       | 36                                       | 59                                       | > 0.90                 |
| DP COMPACT 1200 44W/3000K IP66 GR  | 170 $\mu$ s                   | 34                                       | 29                                       | 46                                       | > 0.90                 |
| DP COMPACT 1200 44 W 4000K IP66 GR | 170 $\mu$ s                   | 34                                       | 29                                       | 46                                       | > 0.90                 |
| DP COMPACT 1200 44 W 6500K IP66 GR | 170 $\mu$ s                   | 34                                       | 29                                       | 46                                       | > 0.90                 |
| DP COMPACT 1500 55W/3000K IP66 GR  | 170 $\mu$ s                   | 32                                       | 26                                       | 42                                       | > 0.90                 |

| Product description                | Inrush current time $T_{H50}$ | Max. no. of lum. on circuit break. B16 A | Max. no. of lum. on circuit break. C10 A | Max. no. of lum. on circuit break. C16 A | Power factor $\lambda$ |
|------------------------------------|-------------------------------|------------------------------------------|------------------------------------------|------------------------------------------|------------------------|
| DP COMPACT 1500 55 W 4000K IP66 GR | 170 $\mu$ s                   | 32                                       | 26                                       | 42                                       | > 0.90                 |
| DP COMPACT 1500 55 W 6500K IP66 GR | 170 $\mu$ s                   | 32                                       | 26                                       | 42                                       | > 0.90                 |

| Product description                | Total harmonic distortion | Protection class | Operating mode        |
|------------------------------------|---------------------------|------------------|-----------------------|
| DP COMPACT 1200 23W/3000K IP66 GR  | 20 %                      | II               | Integrated LED driver |
| DP COMPACT 1200 23 W 4000K IP66 GR | 20 %                      | II               | Integrated LED driver |
| DP COMPACT 1500 31W/3000K IP66 GR  | 20 %                      | II               | Integrated LED driver |
| DP COMPACT 1500 31 W 4000K IP66 GR | 20 %                      | II               | Integrated LED driver |
| DP COMPACT 1200 44W/3000K IP66 GR  | 20 %                      | II               | Integrated LED driver |
| DP COMPACT 1200 44 W 4000K IP66 GR | 20 %                      | II               | Integrated LED driver |
| DP COMPACT 1200 44 W 6500K IP66 GR | 20 %                      | II               | Integrated LED driver |
| DP COMPACT 1500 55W/3000K IP66 GR  | 20 %                      | II               | Integrated LED driver |
| DP COMPACT 1500 55 W 4000K IP66 GR | 20 %                      | II               | Integrated LED driver |
| DP COMPACT 1500 55 W 6500K IP66 GR | 20 %                      | II               | Integrated LED driver |

### Photometrical data

| Product description                | Luminous flux | Luminous efficacy | Color temperature | Light color (designation) | Color rendering index Ra |
|------------------------------------|---------------|-------------------|-------------------|---------------------------|--------------------------|
| DP COMPACT 1200 23W/3000K IP66 GR  | 2600 lm       | 115 lm/W          | 3000 K            | Warm White                | > 80                     |
| DP COMPACT 1200 23 W 4000K IP66 GR | 2800 lm       | 120 lm/W          | 4000 K            | Cool White                | > 80                     |
| DP COMPACT 1500 31W/3000K IP66 GR  | 3500 lm       | 115 lm/W          | 3000 K            | Warm White                | > 80                     |
| DP COMPACT 1500 31 W 4000K IP66 GR | 3800 lm       | 120 lm/W          | 4000 K            | Cool White                | > 80                     |
| DP COMPACT 1200 44W/3000K IP66 GR  | 5100 lm       | 115 lm/W          | 3000 K            | Warm White                | > 80                     |



| Product description                | Luminous flux | Luminous efficacy | Color temperature | Light color (designation) | Color rendering index Ra |
|------------------------------------|---------------|-------------------|-------------------|---------------------------|--------------------------|
| DP COMPACT 1200 44 W 4000K IP66 GR | 5400 lm       | 120 lm/W          | 4000 K            | Cool White                | > 80                     |
| DP COMPACT 1200 44 W 6500K IP66 GR | 5400 lm       | 120 lm/W          | 6500 K            | Cool Daylight             | > 80                     |
| DP COMPACT 1500 55W/3000K IP66 GR  | 6300 lm       | 115 lm/W          | 3000 K            | Warm White                | > 80                     |
| DP COMPACT 1500 55 W 4000K IP66 GR | 6700 lm       | 120 lm/W          | 4000 K            | Cool White                | > 80                     |
| DP COMPACT 1500 55 W 6500K IP66 GR | 6700 lm       | 120 lm/W          | 6500 K            | Cool Daylight             | > 80                     |

| Product description                | Standard deviation of color matching | Luminous intensity | Flickering metric (Pst LM) | Stroboscope effect metric (SVM) | Photobiological safety group acc. to EN62778 |
|------------------------------------|--------------------------------------|--------------------|----------------------------|---------------------------------|----------------------------------------------|
| DP COMPACT 1200 23W/3000K IP66 GR  | ≤5 sdcn                              | -                  | -                          | -                               | RG0                                          |
| DP COMPACT 1200 23 W 4000K IP66 GR | ≤5 sdcn                              | -                  | -                          | -                               | RG0                                          |
| DP COMPACT 1500 31W/3000K IP66 GR  | ≤5 sdcn                              | -                  | -                          | -                               | RG0                                          |
| DP COMPACT 1500 31 W 4000K IP66 GR | ≤5 sdcn                              | -                  | -                          | -                               | RG0                                          |
| DP COMPACT 1200 44W/3000K IP66 GR  | ≤5 sdcn                              | -                  | -                          | -                               | RG0                                          |
| DP COMPACT 1200 44 W 4000K IP66 GR | ≤5 sdcn                              | -                  | -                          | -                               | RG0                                          |
| DP COMPACT 1200 44 W 6500K IP66 GR | ≤5 sdcn                              | -                  | -                          | -                               | RG0                                          |
| DP COMPACT 1500 55W/3000K IP66 GR  | ≤5 sdcn                              | -                  | -                          | -                               | RG0                                          |
| DP COMPACT 1500 55 W 4000K IP66 GR | ≤5 sdcn                              | -                  | -                          | -                               | RG0                                          |
| DP COMPACT 1500 55 W 6500K IP66 GR | ≤5 sdcn                              | -                  | -                          | -                               | RG0                                          |

| Product description                | Beam angle |
|------------------------------------|------------|
| DP COMPACT 1200 23W/3000K IP66 GR  | 120 °      |
| DP COMPACT 1200 23 W 4000K IP66 GR | 120 °      |
| DP COMPACT 1500 31W/3000K IP66 GR  | 120 °      |

| Product description                   | Beam angle |
|---------------------------------------|------------|
| DP COMPACT 1500 31 W 4000K<br>IP66 GR | 120 °      |
| DP COMPACT 1200 44W/3000K<br>IP66 GR  | 120 °      |
| DP COMPACT 1200 44 W 4000K<br>IP66 GR | 120 °      |
| DP COMPACT 1200 44 W 6500K<br>IP66 GR | 120 °      |
| DP COMPACT 1500 55W/3000K<br>IP66 GR  | 120 °      |
| DP COMPACT 1500 55 W 4000K<br>IP66 GR | 120 °      |
| DP COMPACT 1500 55 W 6500K<br>IP66 GR | 120 °      |

### Dimensions & Weight

| Product description                   | Length     | Width    | Height   | Product weight |
|---------------------------------------|------------|----------|----------|----------------|
| DP COMPACT 1200 23W/3000K<br>IP66 GR  | 1290.00 mm | 86.00 mm | 68.00 mm | 1120.00 g      |
| DP COMPACT 1200 23 W 4000K<br>IP66 GR | 1290.00 mm | 86.00 mm | 68.00 mm | 1120.00 g      |
| DP COMPACT 1500 31W/3000K<br>IP66 GR  | 1590.00 mm | 86.00 mm | 68.00 mm | 1350.00 g      |
| DP COMPACT 1500 31 W 4000K<br>IP66 GR | 1590.00 mm | 86.00 mm | 68.00 mm | 1350.00 g      |
| DP COMPACT 1200 44W/3000K<br>IP66 GR  | 1290.00 mm | 86.00 mm | 68.00 mm | 1160.00 g      |
| DP COMPACT 1200 44 W 4000K<br>IP66 GR | 1290.00 mm | 86.00 mm | 68.00 mm | 1160.00 g      |
| DP COMPACT 1200 44 W 6500K<br>IP66 GR | 1290.00 mm | 86.00 mm | 68.00 mm | 1160.00 g      |
| DP COMPACT 1500 55W/3000K<br>IP66 GR  | 1590.00 mm | 86.00 mm | 68.00 mm | 1380.00 g      |
| DP COMPACT 1500 55 W 4000K<br>IP66 GR | 1590.00 mm | 86.00 mm | 68.00 mm | 1380.00 g      |
| DP COMPACT 1500 55 W 6500K<br>IP66 GR | 1590.00 mm | 86.00 mm | 68.00 mm | 1380.00 g      |

### Materials & Colors

| Product description                | Product color | Housing color | Body material      | Cover material     | Light emitting surface material |
|------------------------------------|---------------|---------------|--------------------|--------------------|---------------------------------|
| DP COMPACT 1200 23W/3000K IP66 GR  | Gray          | Gray          | Polycarbonate (PC) | Polycarbonate (PC) | Polycarbonate (PC)              |
| DP COMPACT 1200 23 W 4000K IP66 GR | Gray          | Gray          | Polycarbonate (PC) | Polycarbonate (PC) | Polycarbonate (PC)              |
| DP COMPACT 1500 31W/3000K IP66 GR  | Gray          | Gray          | Polycarbonate (PC) | Polycarbonate (PC) | Polycarbonate (PC)              |
| DP COMPACT 1500 31 W 4000K IP66 GR | Gray          | Gray          | Polycarbonate (PC) | Polycarbonate (PC) | Polycarbonate (PC)              |
| DP COMPACT 1200 44W/3000K IP66 GR  | Gray          | Gray          | Polycarbonate (PC) | Polycarbonate (PC) | Polycarbonate (PC)              |
| DP COMPACT 1200 44 W 4000K IP66 GR | Gray          | Gray          | Polycarbonate (PC) | Polycarbonate (PC) | Polycarbonate (PC)              |
| DP COMPACT 1200 44 W 6500K IP66 GR | Gray          | Gray          | Polycarbonate (PC) | Polycarbonate (PC) | Polycarbonate (PC)              |
| DP COMPACT 1500 55W/3000K IP66 GR  | Gray          | Gray          | Polycarbonate (PC) | Polycarbonate (PC) | Polycarbonate (PC)              |
| DP COMPACT 1500 55 W 4000K IP66 GR | Gray          | Gray          | Polycarbonate (PC) | Polycarbonate (PC) | Polycarbonate (PC)              |
| DP COMPACT 1500 55 W 6500K IP66 GR | Gray          | Gray          | Polycarbonate (PC) | Polycarbonate (PC) | Polycarbonate (PC)              |

| Product description                | Glow Wire Test according to IEC 60695-2-12 | Mercury content |
|------------------------------------|--------------------------------------------|-----------------|
| DP COMPACT 1200 23W/3000K IP66 GR  | 850 °C                                     | 0.0 mg          |
| DP COMPACT 1200 23 W 4000K IP66 GR | 850 °C                                     | 0.0 mg          |
| DP COMPACT 1500 31W/3000K IP66 GR  | 850 °C                                     | 0.0 mg          |
| DP COMPACT 1500 31 W 4000K IP66 GR | 850 °C                                     | 0.0 mg          |
| DP COMPACT 1200 44W/3000K IP66 GR  | 850 °C                                     | 0.0 mg          |
| DP COMPACT 1200 44 W 4000K IP66 GR | 850 °C                                     | 0.0 mg          |
| DP COMPACT 1200 44 W 6500K IP66 GR | 850 °C                                     | 0.0 mg          |
| DP COMPACT 1500 55W/3000K IP66 GR  | 850 °C                                     | 0.0 mg          |
| DP COMPACT 1500 55 W 4000K IP66 GR | 850 °C                                     | 0.0 mg          |
| DP COMPACT 1500 55 W 6500K IP66 GR | 850 °C                                     | 0.0 mg          |

## Application &amp; Mounting

| Product description                | Ambient temperature range | Temperature range at storage | Type of connection         | Type of protection | Protection class IK (shock resistance) |
|------------------------------------|---------------------------|------------------------------|----------------------------|--------------------|----------------------------------------|
| DP COMPACT 1200 23W/3000K IP66 GR  | -35...+50 °C              | -40...+70 °C                 | Screwless terminal, 3-Pole | IP66               | IK08                                   |
| DP COMPACT 1200 23 W 4000K IP66 GR | -35...+50 °C              | -40...+70 °C                 | Screwless terminal, 3-Pole | IP66               | IK08                                   |
| DP COMPACT 1500 31W/3000K IP66 GR  | -35...+50 °C              | -40...+70 °C                 | Screwless terminal, 3-Pole | IP66               | IK08                                   |
| DP COMPACT 1500 31 W 4000K IP66 GR | -35...+50 °C              | -40...+70 °C                 | Screwless terminal, 3-Pole | IP66               | IK08                                   |
| DP COMPACT 1200 44W/3000K IP66 GR  | -35...+50 °C              | -40...+70 °C                 | Screwless terminal, 3-Pole | IP66               | IK08                                   |
| DP COMPACT 1200 44 W 4000K IP66 GR | -35...+50 °C              | -40...+70 °C                 | Screwless terminal, 3-Pole | IP66               | IK08                                   |
| DP COMPACT 1200 44 W 6500K IP66 GR | -35...+50 °C              | -40...+70 °C                 | Screwless terminal, 3-Pole | IP66               | IK08                                   |
| DP COMPACT 1500 55W/3000K IP66 GR  | -35...+50 °C              | -40...+70 °C                 | Screwless terminal, 3-Pole | IP66               | IK08                                   |
| DP COMPACT 1500 55 W 4000K IP66 GR | -35...+50 °C              | -40...+70 °C                 | Screwless terminal, 3-Pole | IP66               | IK08                                   |
| DP COMPACT 1500 55 W 6500K IP66 GR | -35...+50 °C              | -40...+70 °C                 | Screwless terminal, 3-Pole | IP66               | IK08                                   |

| Product description                | Dimmable | Mounting type     | Mounting location | LED module replaceable |
|------------------------------------|----------|-------------------|-------------------|------------------------|
| DP COMPACT 1200 23W/3000K IP66 GR  | No       | Suspended/Surface | Ceiling / Wall    | Not replaceable        |
| DP COMPACT 1200 23 W 4000K IP66 GR | No       | Suspended/Surface | Ceiling / Wall    | Not replaceable        |
| DP COMPACT 1500 31W/3000K IP66 GR  | No       | Suspended/Surface | Ceiling / Wall    | Not replaceable        |
| DP COMPACT 1500 31 W 4000K IP66 GR | No       | Suspended/Surface | Ceiling / Wall    | Not replaceable        |
| DP COMPACT 1200 44W/3000K IP66 GR  | No       | Suspended/Surface | Ceiling / Wall    | Not replaceable        |
| DP COMPACT 1200 44 W 4000K IP66 GR | No       | Suspended/Surface | Ceiling / Wall    | Not replaceable        |
| DP COMPACT 1200 44 W 6500K IP66 GR | No       | Suspended/Surface | Ceiling / Wall    | Not replaceable        |
| DP COMPACT 1500 55W/3000K IP66 GR  | No       | Suspended/Surface | Ceiling / Wall    | Not replaceable        |
| DP COMPACT 1500 55 W 4000K IP66 GR | No       | Suspended/Surface | Ceiling / Wall    | Not replaceable        |

| Product description                   | Dimmable | Mounting type     | Mounting location | LED module replaceable |
|---------------------------------------|----------|-------------------|-------------------|------------------------|
| DP COMPACT 1500 55 W 6500K<br>IP66 GR | No       | Suspended/Surface | Ceiling / Wall    | Not replaceable        |

### Lifespan

| Product description                   | Lifespan L70/B50 at<br>25 °C | Lifespan L80/B10 at<br>25 °C | Lifespan L90/B10 at<br>25 °C | Number of switching<br>cycles |
|---------------------------------------|------------------------------|------------------------------|------------------------------|-------------------------------|
| DP COMPACT 1200 23W/3000K<br>IP66 GR  | 50000 h                      | 35000 h                      | 20000 h                      | 100000                        |
| DP COMPACT 1200 23 W 4000K<br>IP66 GR | 50000 h                      | 35000 h                      | 20000 h                      | 100000                        |
| DP COMPACT 1500 31W/3000K<br>IP66 GR  | 50000 h                      | 35000 h                      | 20000 h                      | 100000                        |
| DP COMPACT 1500 31 W 4000K<br>IP66 GR | 50000 h                      | 35000 h                      | 20000 h                      | 100000                        |
| DP COMPACT 1200 44W/3000K<br>IP66 GR  | 50000 h                      | 35000 h                      | 20000 h                      | 100000                        |
| DP COMPACT 1200 44 W 4000K<br>IP66 GR | 50000 h                      | 35000 h                      | 20000 h                      | 100000                        |
| DP COMPACT 1200 44 W 6500K<br>IP66 GR | 50000 h                      | 35000 h                      | 20000 h                      | 100000                        |
| DP COMPACT 1500 55W/3000K<br>IP66 GR  | 50000 h                      | 35000 h                      | 20000 h                      | 100000                        |
| DP COMPACT 1500 55 W 4000K<br>IP66 GR | 50000 h                      | 35000 h                      | 20000 h                      | 100000                        |
| DP COMPACT 1500 55 W 6500K<br>IP66 GR | 50000 h                      | 35000 h                      | 20000 h                      | 100000                        |

### Certificates & Standards

| Product description                   | Standards                         | Luminaire with limited surface temperature, "D<br>sign" | Ball shot<br>safe |
|---------------------------------------|-----------------------------------|---------------------------------------------------------|-------------------|
| DP COMPACT 1200 23W/3000K<br>IP66 GR  | CE / CB / TÜV SÜD / EAC /<br>RoHS | Yes                                                     | No                |
| DP COMPACT 1200 23 W 4000K<br>IP66 GR | CE / CB / TÜV SÜD / EAC /<br>RoHS | Yes                                                     | No                |
| DP COMPACT 1500 31W/3000K<br>IP66 GR  | CE / CB / TÜV SÜD / EAC /<br>RoHS | Yes                                                     | No                |
| DP COMPACT 1500 31 W 4000K<br>IP66 GR | CE / CB / TÜV SÜD / EAC /<br>RoHS | Yes                                                     | No                |
| DP COMPACT 1200 44W/3000K<br>IP66 GR  | CE / CB / TÜV SÜD / EAC /<br>RoHS | Yes                                                     | No                |
| DP COMPACT 1200 44 W 4000K<br>IP66 GR | CE / CB / TÜV SÜD / EAC /<br>RoHS | Yes                                                     | No                |

| Product description                | Standards                      | Luminaire with limited surface temperature, "D sign" | Ball shot safe |
|------------------------------------|--------------------------------|------------------------------------------------------|----------------|
| DP COMPACT 1200 44 W 6500K IP66 GR | CE / CB / TÜV SÜD / EAC / RoHS | Yes                                                  | No             |
| DP COMPACT 1500 55W/3000K IP66 GR  | CE / CB / TÜV SÜD / EAC / RoHS | Yes                                                  | No             |
| DP COMPACT 1500 55 W 4000K IP66 GR | CE / CB / TÜV SÜD / EAC / RoHS | Yes                                                  | No             |
| DP COMPACT 1500 55 W 6500K IP66 GR | CE / CB / TÜV SÜD / EAC / RoHS | Yes                                                  | No             |

## EQUIPMENT / ACCESSORIES

- Stainless steel clamps with safety screws included
- Mounting accessories included (suspension kit, theft protection kit)

## APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

## SALES AND TECHNICAL SUPPORT

Sales and Technical Support [www.ledvance.com](http://www.ledvance.com)

## COUNTRY SPECIFIC INFORMATION

| Product description                | Product code  | METEL-Code | SEG number | STK number | UK Org |
|------------------------------------|---------------|------------|------------|------------|--------|
| DP COMPACT 1200 23W/3000K IP66 GR  | 4058075424227 | -          | 7215489    | 4315593    | -      |
| DP COMPACT 1200 23 W 4000K IP66 GR | 4058075210028 | -          | 7214983    | 4315525    | -      |
| DP COMPACT 1500 31W/3000K IP66 GR  | 4058075424265 | -          | 7215491    | 4315595    | -      |
| DP COMPACT 1500 31 W 4000K IP66 GR | 4058075210080 | -          | 7214986    | 4315540    | -      |
| DP COMPACT 1200 44W/3000K IP66 GR  | 4058075424241 | -          | 7215490    | 4315594    | -      |
| DP COMPACT 1200 44 W 4000K IP66 GR | 4058075210042 | -          | 7214984    | 4315538    | -      |
| DP COMPACT 1200 44 W 6500K IP66 GR | 4058075210066 | -          | 7214985    | 4315539    | -      |
| DP COMPACT 1500 55W/3000K IP66 GR  | 4058075424289 | -          | 7215492    | 4315596    | -      |
| DP COMPACT 1500 55 W 4000K IP66 GR | 4058075210103 | -          | 7214987    | 4315541    | -      |
| DP COMPACT 1500 55 W 6500K IP66 GR | 4058075210127 | -          | 7214988    | 4315542    | -      |

## DOWNLOAD DATA

| DOWNLOAD DATA                                                                       |                                                                    |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------|
|     | User instruction<br>DAMPPROOF COMPACT IP66                         |
|    | Tender documents<br>Tender Text 4058075424227                      |
|     | Declarations of conformity<br>DP COMPACT                           |
|    | IES file (IES)<br>DP Compact 1200 23W 3000K GR IP66                |
|    | LDT file (Eulumdat)<br>DP Compact 1200 23W 3000K GR IP66           |
|    | R3D file (Relux 3D Model)<br>dampproof compact 1200                |
|    | M3D file (3D Model)<br>Dampproof Compact 1200                      |
|    | UGR file (UGR table)<br>DP Compact 1200 23W 3000K GR IP66          |
|    | User instruction<br>DAMPPROOF COMPACT IP66                         |
|  | Tender documents<br>Tender Text 4058075210028                      |
|   | Declarations of conformity<br>EC Declaration of Damp Proof Compact |
|  | IES file (IES)<br>DP Compact 1200 23W 4000K GR IP66                |
|  | LDT file (Eulumdat)<br>DP Compact 1200 23W 4000K GR IP66           |
|  | R3D file (Relux 3D Model)<br>DAMP PROOF COMPACT 1200               |
|  | M3D file (3D Model)<br>DAMP PROOF COMPACT 1200                     |
|  | UGR file (UGR table)<br>DP Compact 1200 23W 4000K GR IP66          |
|   | User instruction<br>DAMPPROOF COMPACT IP66                         |
|  | Tender documents<br>Tender Text 4058075424265                      |

| DOWNLOAD DATA                                                                       |                                                                    |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------|
|     | Declarations of conformity<br>DP COMPACT                           |
|    | IES file (IES)<br>DP Compact 1500 31W 3000K IP66 GR                |
|    | LDT file (Eulumdat)<br>DP Compact 1500 31W 3000K IP66 GR           |
|    | R3D file (Relux 3D Model)<br>Dampproof Compact 1500                |
|    | M3D file (3D Model)<br>Dampproof Compact 1500                      |
|    | UGR file (UGR table)<br>DP Compact 1500 31W 3000K IP66 GR          |
|     | User instruction<br>DAMPPROOF COMPACT IP66                         |
|    | Tender documents<br>Tender Text 4058075210080                      |
|    | Declarations of conformity<br>EC Declaration of Damp Proof Compact |
|  | IES file (IES)<br>DP Compact 1500 31W 4000K GR IP66                |
|  | LDT file (Eulumdat)<br>DP Compact 1500 31W 4000K GR IP66           |
|  | R3D file (Relux 3D Model)<br>DAMP PROOF COMPACT 1500               |
|  | M3D file (3D Model)<br>DAMP PROOF COMPACT 1500                     |
|  | UGR file (UGR table)<br>DP Compact 1500 31W 4000K GR IP66          |
|   | User instruction<br>DAMPPROOF COMPACT IP66                         |
|  | Tender documents<br>Tender Text 4058075424241                      |
|   | Declarations of conformity<br>DP COMPACT                           |
|  | IES file (IES)<br>DP Compact 1200 44W 3000K GR IP66                |

| DOWNLOAD DATA                                                                       |                                                                    |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------|
|    | LDT file (Eulumdat)<br>DP Compact 1200 44W 3000K GR IP66           |
|    | R3D file (Relux 3D Model)<br>dampproof compact 1200                |
|    | M3D file (3D Model)<br>Dampproof Compact 1200                      |
|    | UGR file (UGR table)<br>DP Compact 1200 44W 3000K GR IP66          |
|     | User instruction<br>DAMPPROOF COMPACT IP66                         |
|    | Tender documents<br>Tender Text 4058075210042                      |
|     | Declarations of conformity<br>EC Declaration of Damp Proof Compact |
|    | IES file (IES)<br>DP Compact 1200 44W 4000K GR IP66                |
|   | LDT file (Eulumdat)<br>DP Compact 1200 44W 4000K GR IP66           |
|  | R3D file (Relux 3D Model)<br>DAMP PROOF COMPACT 1200               |
|  | M3D file (3D Model)<br>DAMP PROOF COMPACT 1200                     |
|  | UGR file (UGR table)<br>DP Compact 1200 44W 4000K GR IP66          |
|   | User instruction<br>DAMPPROOF COMPACT IP66                         |
|  | Tender documents<br>Tender Text 4058075210066                      |
|   | Declarations of conformity<br>EC Declaration of Damp Proof Compact |
|  | IES file (IES)<br>DP Compact 1200 44W 6500K GR IP66                |
|  | LDT file (Eulumdat)<br>DP Compact 1200 44W 6500K GR IP66           |
|  | R3D file (Relux 3D Model)<br>DAMP PROOF COMPACT 1200               |

| DOWNLOAD DATA                                                                       |                                                                    |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------|
|    | M3D file (3D Model)<br>DAMP PROOF COMPACT 1200                     |
|    | UGR file (UGR table)<br>DP Compact 1200 44W 6500K GR IP66          |
|     | User instruction<br>DAMPPROOF COMPACT IP66                         |
|    | Tender documents<br>Tender Text 4058075424289                      |
|     | Declarations of conformity<br>DP COMPACT                           |
|    | IES file (IES)<br>DP Compact 1500 55W 3000K IP66 GR                |
|    | LDT file (Eulumdat)<br>DP Compact 1500 55W 3000K IP66 GR           |
|    | R3D file (Relux 3D Model)<br>Dampproof Compact 1500                |
|   | M3D file (3D Model)<br>Dampproof Compact 1500                      |
|  | UGR file (UGR table)<br>DP Compact 1500 55W 3000K IP66 GR          |
|   | User instruction<br>DAMPPROOF COMPACT IP66                         |
|  | Tender documents<br>Tender Text 4058075210103                      |
|   | Declarations of conformity<br>EC Declaration of Damp Proof Compact |
|  | IES file (IES)<br>DP Compact 1500 55W 4000K GR IP66                |
|  | LDT file (Eulumdat)<br>DP Compact 1500 55W 4000K GR IP66           |
|  | R3D file (Relux 3D Model)<br>DAMP PROOF COMPACT 1500               |
|  | M3D file (3D Model)<br>DAMP PROOF COMPACT 1500                     |
|  | UGR file (UGR table)<br>DP Compact 1500 55W 4000K GR IP66          |

## DOWNLOAD DATA






|                                                                                   |                                                                    |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------|
|   | User instruction<br>DAMPPROOF COMPACT IP66                         |
|  | Tender documents<br>Tender Text 4058075210127                      |
|   | Declarations of conformity<br>EC Declaration of Damp Proof Compact |
|  | IES file (IES)<br>DP Compact 1500 55W 6500K GR IP66                |
|  | LDT file (Eulumdat)<br>DP Compact 1500 55W 6500K GR IP66           |
|  | R3D file (Relux 3D Model)<br>DAMP PROOF COMPACT 1500               |
|  | M3D file (3D Model)<br>DAMP PROOF COMPACT 1500                     |
|  | UGR file (UGR table)<br>DP Compact 1500 55W 6500K GR IP66          |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075424227 | Folding box<br>1             | 72 mm x 1,319 mm x 90 mm             | 1310.00 g    | 8.55 dm <sup>3</sup>  |
| 4058075210028 | Folding box<br>1             | 72 mm x 1,319 mm x 90 mm             | 1270.00 g    | 8.55 dm <sup>3</sup>  |
| 4058075424265 | Folding box<br>1             | 72 mm x 1,619 mm x 90 mm             | 1540.00 g    | 10.49 dm <sup>3</sup> |
| 4058075210080 | Folding box<br>1             | 72 mm x 1,619 mm x 90 mm             | 1540.00 g    | 10.49 dm <sup>3</sup> |
| 4058075424241 | Folding box<br>1             | 72 mm x 1,319 mm x 90 mm             | 1310.00 g    | 8.55 dm <sup>3</sup>  |
| 4058075210042 | Folding box<br>1             | 72 mm x 1,319 mm x 90 mm             | 1310.00 g    | 8.55 dm <sup>3</sup>  |
| 4058075210066 | Folding box<br>1             | 72 mm x 1,319 mm x 90 mm             | 1310.00 g    | 8.55 dm <sup>3</sup>  |
| 4058075424289 | Folding box<br>1             | 72 mm x 1,619 mm x 90 mm             | 1570.00 g    | 10.49 dm <sup>3</sup> |
| 4058075210103 | Folding box<br>1             | 72 mm x 1,619 mm x 90 mm             | 1570.00 g    | 10.49 dm <sup>3</sup> |
| 4058075210127 | Folding box<br>1             | 72 mm x 1,619 mm x 90 mm             | 1570.00 g    | 10.49 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### ADDITIONAL CATALOG INFORMATION



### References / Links

- For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.